

# HARDOX® 400 PLATE

2025-05-22

The table shows available dimensions in mm for direct order including the maximum length.

Some restrictions, contact your local sales representative for more information

Outside the range of dimensions

Minimum length: 2000 mm<sup>1)</sup>

Minimum quantities:

|             |                       |
|-------------|-----------------------|
| Thickness:  | Min. position weight: |
| 4.0-60.0    | 2.5 tons              |
| 60.1-100.0  | 3.5 tons              |
| 100.1-120.0 | 4.0 tons              |
| 120.1-      | 5.0 tons              |

| Width         | 1000- | 1351- | 1501- | 1601- | 1701- | 1801- | 1901- | 2001- | 2101- | 2201- | 2301- | 2401- | 2501- | 2601- | 2701- | 2751- | 2801- | 2901- | 3001- | 3101- | 3201- | 3301- |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Thickness     | 1350  | 1500  | 1600  | 1700  | 1800  | 1900  | 2000  | 2100  | 2200  | 2300  | 2400  | 2500  | 2600  | 2700  | 2750  | 2800  | 2900  | 3000  | 3100  | 3200  | 3300  | 3350  |
| 3.2 - 3.9     |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 4.0 - 4.7     |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 4.8 - 6.0     |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 6.1 - 6.7     |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 6.8 - 7.7     |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 7.8 - 8.7     |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 8.8 - 10.0    |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 10.1 - 25.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 25.1 - 26.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 26.1 - 27.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 27.1 - 28.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 28.1 - 29.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 29.1 - 30.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 30.1 - 31.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 31.1 - 32.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 32.1 - 33.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 33.1 - 34.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 34.1 - 35.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 35.1 - 36.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 36.1 - 37.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 37.1 - 38.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 38.1 - 39.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 39.1 - 40.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 40.1 - 45.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 45.1 - 50.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 50.1 - 55.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 55.1 - 60.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 60.1 - 65.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 65.1 - 70.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 70.1 - 75.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 75.1 - 80.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 80.1 - 85.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 85.1 - 90.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 90.1 - 95.0   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 95.1 - 100.0  |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 100.1 - 105.0 |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 105.1 - 110.0 |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 110.1 - 115.0 |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 115.1 - 120.0 |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 120.1 - 125.0 |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 125.1 - 130.0 |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 130.1 - 135.0 |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 135.1 - 140.0 |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 140.1 - 150.0 |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 150.1 - 160   |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |

<sup>1)</sup> Minimum length when ordering one single plate is 3700 mm. Minimum order quantity is 2 plates when order length is less than 3700 mm.

# HARDOX® 400 SHEET

The table shows available dimensions mm for direct order including maximum length.  
Cut lengths with mill edges, black

Some restrictions, please contact product manager or Tech support

Outside the range of dimensions

Min. length 1500 mm  
Min. bundle weight 2 tons

| Width       | 950- | 1001- | 1201- | 1251- | 1301- | 1501- | 1526- | 1551- | 1576- | 1601- | 1626- |
|-------------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Thickness   | 1000 | 1200  | 1250  | 1300  | 1500  | 1525  | 1550  | 1575  | 1600  | 1625  | 1650  |
| 2.00 - 2.49 |      |       |       |       |       |       |       |       |       |       |       |
| 2.50 - 2.99 |      |       |       |       |       |       |       |       |       |       |       |
| 3.00 - 3.49 |      |       |       |       |       |       |       |       |       |       |       |
| 3.50 - 3.99 |      |       |       |       |       |       |       |       |       |       |       |
| 4.00 - 4.49 |      |       |       |       |       |       |       |       |       |       |       |
| 4.50 - 4.79 |      |       |       |       |       |       |       |       |       |       |       |
| 4.80 - 4.99 |      |       |       |       |       |       |       |       |       |       |       |
| 5.00 - 5.99 |      |       |       |       |       |       |       |       |       |       |       |
| 6.00 - 6.40 |      |       |       |       |       |       |       |       |       |       |       |
| 6.41 - 6.50 |      |       |       |       |       |       |       |       |       |       |       |
| 6.51 - 6.99 |      |       |       |       |       |       |       |       |       |       |       |
| 7.00 - 8.00 |      |       |       |       |       |       |       |       |       |       |       |
| 8.10 - 10.0 |      |       |       |       |       |       |       |       |       |       |       |
| 10.1 - 25.0 |      |       |       |       |       |       |       |       |       |       |       |
| 25.1 - 26.0 |      |       |       |       |       |       |       |       |       |       |       |
| 26.1 - 27.0 |      |       |       |       |       |       |       |       |       |       |       |

Min position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width.  
Delivery weight accuracy +/- 10 %, at least -2 tons / + 3 tons.